



Product information EF12LW4 Au 933 395-200

| Name | EF12LW4 Au |
|-----------------------------------|--|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | Horizontal appliance socket for combined front panels and circuit board installation with 2 metal screws, 2 x 0-rings |
| Delivery informations | Les basses with the |
| Availability | no longer available |
| Product description | Harizantal appliance cookst for combined front people and circuit heard installation with 2 motel assaure 2 v 0 since |
| Description | Horizontal appliance socket for combined front panels and circuit board installation with 2 metal screws, 2 x 0-rings EF12LW4 Au |
| Type | |
| Order No. Type of contact | 933 395-200 |
| Number of contacts | female 4 |
| Standard | |
| Housing Color | IEC 61076-2-101 (Ed. 1)/ IEC 60947-5-2 |
| Technical data | metallic |
| Rated voltage | AC/DC 150 V |
| Rated current | 4A |
| Type of termination | solder, solid pins diameter 1 mm |
| Material | Street, state pure data see: 1 min |
| Contact material | Cu Zn |
| Contact surface material | Au |
| Contact bearer material | PA |
| Housing material | Cu Zn/Ni |
| 0-Ring | NBR |
| Environmental conditions | |
| Protection class (IEC 60529) | IP 68 |
| Pollution severity | 3 |
| Temperature range | -25 °C to +90 °C |
| Inflammability class | |
| Contact bearer | 94 V-2 |
| Approvals | |
| UL | UL pending |
| Packing unit | |
| Packaging unit | 100 pieces |
| Scope of delivery and accessories | 200 Miles 200 Mi |
| Accessories to order separately | protective cap M12 VS, |
| | order no. 734 209-100 |

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.