



Product information M1-8TP-RJ45 PoE 942 028-001

Name	M1-8TP-RJ45 P0E
	Dr. 1995 Was
	4
	8 x 10/100BaseTX PoE+ RJ45 port media module for modular, managed, Industrial Workgroup Switch MACH102
Delivery informations	
Availability	available
Product description	
Description	8 x 10/100BaseTX PoE+ RJ45 port media module for modular, managed, Industrial Workgroup Switch MACH102
Туре	M1-8TP-RJ45 P0E
Order No.	942-028 001
Network size - length of cable	
Twisted pair (TP)	0 m 100 m
Power requirements	
Power consumption	2.2 W (plus up to 120 W PoE per external power supply)
Ambient conditions	
Operating temperature	0 °C 50 °C
Storage/transport temperature	-20 °C 85 °C
Relative humidity (non-condensing)	10 % 95 %
Mechanical construction	
Dimensions (W x H x D)	138 x 42 x 90
Mounting	Media Module
Protection class	IP20
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-2700 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	CUL 508
Scope of delivery and accessories	
Scope of delivery	Media module, user manual

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.