



**Product information**  
**Compact OpenRail Gigabit Ethernet Switch 8-24 ports -**  
**RS30-08020606SDAEHH07.0.**  
**943 434-031**

<b>Name</b>		<b>Compact OpenRail Gigabit Ethernet Switch 8-24 ports</b>	
			
		10 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 8 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design	
<b>Delivery informations</b>			
<b>Availability</b>		available	
<b>Product description</b>			
<b>Description</b>		10 port Gigabit/Fast-Ethernet-Switch (2 x Gigabit Ethernet, 8 x Fast Ethernet), managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design	
<b>Port type and quantity</b>		10 Ports in total, 2 Gigabit Ethernet ports; 1. uplink: Gigabit SFP-Slot; 2. uplink: Gigabit SFP-Slot; 8 x standard 10/100 BASE TX, RJ45	
<b>Type</b>		RS30-08020606SDAEHH07.0.	
<b>Order No.</b>		943 434-031	
<b>More Interfaces</b>			
<b>Power supply/signaling contact</b>		1 x plug-in terminal block, 6-pin	
<b>V.24 interface</b>		1 x RJ11 socket	
<b>USB interface</b>		1 x USB to connect the AutoConfiguration Adapter ACA21-USB	
<b>Network size - length of cable</b>			
<b>Multimode fiber (MM) 50/125 µm</b>		cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC	
<b>Multimode fiber (MM) 62.5/125 µm</b>		cf. SFP LWL module M-SFP-SX/LC and M-SFP-LX/LC	
<b>Single mode fiber (SM) 9/125 µm</b>		cf. SFP LWL module M-SFP-LX/LC	
<b>Single mode fiber (LH) 9/125 µm (long haul transceiver)</b>		cf. SFP LWL module M-SFP-LH/LC und M-SFP-LH+/LC	
<b>Network size - cascading</b>			
<b>Line - / star topology</b>		any	
<b>Ring structure (HIPER-Ring) quantity switches</b>		50 (reconfiguration time < 0.3 sec.)	
<b>Power requirements</b>			
<b>Operating voltage</b>		12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V (redundant)	
<b>Current consumption at 24 V DC</b>		320 mA	
<b>Current consumption at 48 V DC</b>		172 mA	
<b>Power output in Btu (IT) h</b>		26.3	
<b>Software</b>			
<b>Management</b>		Serial interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP	
<b>Diagnostics</b>		LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1, topology discovery 802.1AB, disable learning, SFP diagnostic (temperature, optical input and output power, power in dBm)	
<b>Configuration</b>		Comand line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HIDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic invalid configuration undo,	
<b>Security</b>		Port Security (IP und MAC) with multiple addresses, SNMP V3 (no encryption)	
<b>Redundancy functions</b>		HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, MRP and RSTP in parallel, redundant 24 V power supply	
<b>Filter</b>		QoS 4 classes, port prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, multicast (IGMP Snooping/Querier), multicast detection unknown multicast, broadcastlimiter, fast aging	
<b>Industrial Profiles</b>		EtherNet/IP and PROFINET (2.2 PDEV, GSDML stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix	
<b>Time synchronisation</b>		SNTP client/server, PTP / IEEE 1588	
<b>Flow control</b>		Flow control 802.3x, port priority 802.1D/p, priority (TOS/DIFFSERV)	

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



<b>Presettings</b>	Standard
<b>Ambient conditions</b>	
<b>Operating temperature</b>	0 °C ... 60 °C
<b>Storage/transport temperature</b>	-40 °C ... 70 °C
<b>Relative humidity (non-condensing)</b>	10 % ... 95 %
<b>MTBF</b>	52.7 years (MIL-HDBK-217F)
<b>Protective paint on PCB</b>	No
<b>Mechanical construction</b>	
<b>Dimensions (W x H x D)</b>	74 mm x 131 mm x 111 mm
<b>Mounting</b>	DIN Rail
<b>Weight</b>	410 gram
<b>Protection class</b>	IP20
<b>Mechanical stability</b>	
<b>IEC 60068-2-27 shock</b>	15 g, 11 ms duration, 18 shocks
<b>IEC 60068-2-6 vibration</b>	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
<b>EMC interference immunity</b>	
<b>EN 61000-4-2 electrostatic discharge (ESD)</b>	6 kV contact discharge, 8 kV air discharge
<b>EN 61000-4-3 electromagnetic field</b>	10 V/m (80-1000 MHz)
<b>EN 61000-4-4 fast transients (burst)</b>	2 kV power line, 1 kV data line
<b>EN 61000-4-5 surge voltage</b>	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
<b>EN 61000-4-6 conducted immunity</b>	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
<b>EMC emitted immunity</b>	
<b>FCC CFR47 Part 15</b>	FCC 47 CFR Part 15 Class A
<b>EN 55022</b>	EN 55022 Class A
<b>Approvals</b>	
<b>Safety of industrial control equipment</b>	cUL 508
<b>Hazardous locations</b>	cUL 1604 Class1 Div 2
<b>Shipbuilding</b>	n/a
<b>Railway norm</b>	n/a
<b>Substation</b>	n/a
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	Device, terminal block, operating manual