



Product information
M-FAST SFP-TX/RJ45 EEC

942 098-002

Name	M-FAST SFP-TX/RJ45 EEC
	SFP TX Fast Ethernet Transceiver, 100 Mbit/s full duplex auto neg. fixed, cable crossing not supported
Delivery informations	
Availability	available
Product description	
Description	SFP TX Fast Ethernet Transceiver, 100 Mbit/s full duplex auto neg. fixed, cable crossing not supported
Port type and quantity	1 x 100BASE-T with RJ45-socket
Type	M-FAST SFP-TX/RJ45 EEC
Order No.	942 098-002
Power requirements	
Operating voltage	power supply via the switch
Power consumption	1 W
Ambient conditions	
Operating temperature	-40 °C to +70 °C
Storage/transport temperature	-40°C to +85°C
Relative humidity (non-condensing)	10% to 95%
MTBF	67 years (Telcordia GR-468-CORE)
Mechanical construction	
Dimensions (W x H x D)	14 mm x 14 mm x 70 mm
Mounting	SFP slot
Weight	40 g
Protection class	IP 20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz - 13.2 Hz, 90 min. 0.7g, 13.2 Hz - 100 Hz, 90 min. 3.5 mm, 3 Hz - 9 Hz, 10 cycles, 1 octave/min. 1g, 9 Hz - 150 Hz, 10 cycles, 1 octave/min.
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80 - 1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz - 150 kHz), 10 V (150 kHz - 80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC CFR47 Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 60950-1
Scope of delivery and accessories	
Scope of delivery	SFP module