

Article**500.M1687**

INTERLOCKED SOCKET 3P+N+E IP44 16A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.642 KG
EAN code	8001636120447
INTRASTAT code	85366990

TechData

Syntetical description	INTERLOCKED SOCKET
Commercial series	OMNIA Series
Protection degree	IP44
Flange	136X125MM_PAR
Rated current	16A
Poles	3P+N+E
Working frequency	50Hz
Working frequency	60Hz
Rated voltage	346-415V
Colour	RED
Hour position	6h

Approvals and Certifications

I.M.Q. - ENEC 03
 European Norms Electrical Certification



CE
 Declaration of conformity

Standards and Laws

EN 60309-1 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636544700
Gross weight	4.236 KG
Volume	17812.5 CCM
Dimensions	150x475x250 (MM)

Annexed

Note:

Blank side with drilling point mark

