

Article**500.M3283**

INTERLOCKED SOCKET 2P+E IP44 32A 6h

Picture**Master data**

Minimum order	1 NR
Net Weight	0.638 KG
EAN code	8001636120515
INTRASTAT code	85366990

TechData

Syntetical description	INTERLOCKED SOCKET
Commercial series	OMNIA Series
Protection degree	IP44
Flange	136X125MM_PAR
Rated current	32A
Poles	2P+E
Working frequency	50Hz
Working frequency	60Hz
Rated voltage	200-250V
Colour	BLUE
Hour position	6h

Approvals and Certifications

I.M.Q. - ENEC 03

European Norms Electrical Certification



CE

Declaration of conformity

Standards and Laws

EN 60309-1 (1999)

[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2 (1999)

[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-1/A1 (2007)

[European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A1 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4 (2007)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Switched socket-outlets and connectors, with or without interlock



EN 60309-1/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 1: General requirements



EN 60309-2/A2 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. Part 2: Dimensional interchangeability requirements for pin and contact-tube accessories of harmonized configurations



EN 60309-4/A1 (2012)
 [European Standard] Plugs, socket-outlets and couplers for industrial purposes. - Switched socket-outlets and connectors, with or without interlock

Packaging

Description	Carton
Quantity	6
EAN code	8001636544779
Gross weight	4.398 KG
Volume	18427.5 CCM
Dimensions	315x390x150 (MM)

Annexed



Technical drawing [DWG]



Technical drawing [PDF]



Technical drawing [STP]

Note:

Blank side with drilling point mark

