



**Product:** [OCTOPUS 8TX PoE-EEC](#)

Unmanged IP67 PoE-Switch, 8 ports, supply voltage 24 VDC, train approvals

**Product Description**

Configurable IP67 switch in accordance with IEEE 802.3, PoE+ in accordance with IEEE 802.3at, Store-and-Forward-Switching, Ethernet (10 Mbit/s) and Fast-Ethernet (100 Mbit/s)

**Technical Drawing**



**Technical Specifications**

**Product description**

Type:	OCTOPUS 8TX PoE-EEC
Description:	The OCTOPUS switches are suited for outdoor applications with rough environmental conditions. Because of the branch typical approvals they can be used in transport applications (E1), as well as in trains (EN 50155) and ships (GL).
Part Number:	942151001

Port type and quantity:	8 x 10/100 BASE-TX thereof 7 PoE+, M12 D coding, 4-pole, TP cable, auto-crossing, auto-negotiation, auto-polarity
-------------------------	---

## More Interfaces

Power supply/signaling contact:	1 x M12 5-pin connector, A coding, no signaling contact
USB interface:	1 x M12 5-pin socket, A coding

## Network size - length of cable

Twisted pair (TP):	0-100 m
--------------------	---------

## Network size - cascability

Line - / star topology:	any
-------------------------	-----

## Power requirements

Operating Voltage:	24 VDC (16.8 .. 32 VDC)
Power consumption:	max. 44 W with 35W PoE output
Power output in BTU (IT)/h:	max. . 30.7
Redundancy functions:	redundant power supply

## Software

Diagnostics:	LEDs (power, link status, data, PoE-status)
Configuration:	Switch: aging time, QoS 802.1p mapping, QoS DSCP mapping. Pro Port: port state, flow control, broadcast mode, multicast mode, jumbo frames, QoS trust mode, port-based priority, auto-negotiation, data rate, duplex mode, auto-crossing, MDI state. Pro PoE Port: PoE enable, PoE priority, PoE allowed classes

## Ambient conditions

Operating temperature:	-40-+70 °C
Note:	Please note that some recommended accessory parts only support a temperature range from -25 °C to +70 °C and might limit the possible operating conditions for the entire system.
Storage/transport temperature:	-40-+85 °C
Relative humidity (also condensing):	5-100 %

## Mechanical construction

Dimensions (W x H x D):	61 mm x 201 mm x 46 mm
Weight:	910 g
Mounting:	Wall mounting
Protection class:	IP65 , IP67

## Mechanical stability

IEC 60068-2-6 vibration:	1 mm, 2 Hz-13.2 Hz, 90 min. 0.7 g, 13.2 Hz-100 Hz, 90 min. 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min. 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
IEC 60068-2-27 shock:	15 g, 11 ms duration, 18 shocks

## EMC interference immunity

EN 61000-4-2 electrostatic discharge (ESD):	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field:	20 V/m (80-3000 MHz)
EN 61000-4-4 fast transients (burst):	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage:	power line: 2 kV (line/earth), 1 kV (line/line), 2 kV data line
EN 61000-4-6 Conducted Immunity:	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)

## EMC emitted immunity

EN 55032:	EN 55032 Class A
FCC CFR47 Part 15:	FCC 47CFR Part 15, Class A

## Approvals

Basis Standard:	CE, EAC, Australian Regulatory Compliance Mark (RCM)
Safety of industrial control equipment:	cUL61010-2-201
Hazardous locations:	ISA 12.12.01 Class 1 Div. 2

Railway norm:	EN 50155, EN 45545-2, EN 50121-4
Transportation:	E1

## Scope of delivery and accessories

Accessories to Order Separately:	ACA22-M12 (EEC) (942 125-001), M12 connector, "D"-coded (934 445-001) 2 m cordset with M12-connector, "D"-coded (934 578-001) 5 m cordset with M12-connectors, "D"-coded (934 578-002) 10 m cordset with M12-connectors, "D"-coded (934 578-003) Bulkhead M12 "D"-coded to RJ45 (934 498-001), OCTOPUS metal dust cover set (25 pieces) (942 057-001), OCTOPUS plastic dust cover set (25 pieces) (942 057-002)*
Scope of delivery:	1 × Device, 1 × Transport protection cap for supply voltage connection, 7 × Protection cap for M12 socket, 1 x M12-connector (ELWIK A 5012 PG7) for power connection, General safety instructions
Update and Revision:	Revision Number: 0.37 Revision Date: 07-24-2020

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.