



Product information
ASB 8/LED 5-4/1.5 M
11116

Name	
ASB 8/LED 5-4/1.5 M	
	
	Actuator/sensor distribution box, 8-port version, with LED operation and function indicators and single wire connection on the rear, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, 1.5 meter.
Delivery informations	
Availability	available
Product description	
Type	ASB 8/LED 5-4/1.5 M
Order No.	11116
Description	Actuator/sensor distribution box, 8-port version, with LED operation and function indicators and single wire connection on the rear, combined FIXCON-/M12 socket, 4-pole, 1 signal per socket, earth connection, 1.5 meter.
Number of contacts	4 (M12)
Version	8 ports
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Mechanical data	
Thread	M12
LED display present	✔
Environmental conditions	
Environmental temperature	-15 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	PA-GF, self-extinguishing
Contact material	CuZn (M12)
Contact material - Surface refinement	pre-nickel and 0.8 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤ 5 mΩ
Rated current In	4 A per socket / 12 A max. at 40°C
Nominal voltage	10 - 30 V DC
Rated voltage	32 V
Insulation resistance	> 1 GΩ
Approvals	
Approvals	cURus
Cable	
Cable length	1.5 m
Scope of delivery and accessories	
Scope of delivery	ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

