



**Product information**

**ASBS 6/LED 5-4**

**11128**

<b>Name</b>	
Name	ASBS 6/LED 5-4
	
	Pluggable actuator/sensor distribution box, 6 port version, with LED operation and function indicators, combined FIXCOM/M12 socket, 4-pole, 1 signal per socket, earth connection, M23 connection for the control cable.
<b>Delivery informations</b>	
Availability	available
<b>Product description</b>	
Type	ASBS 6/LED 5-4
Order No.	11128
Description	Pluggable actuator/sensor distribution box, 6 port version, with LED operation and function indicators, combined FIXCOM/M12 socket, 4-pole, 1 signal per socket, earth connection, M23 connection for the control cable.
Number of contacts	4 (M12)
Version	6 ports
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance
<b>Classification</b>	
Belden brand	Lumberg-Automation
<b>Mechanical data</b>	
Thread	M12
LED display present	✔
<b>Environmental conditions</b>	
Environmental temperature	-15 °C ... 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
<b>Materials</b>	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	PA-GF, self-extinguishing
Contact material	CuZn
Contact material - Surface refinement	pre-nickel and 0.8 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
<b>Electrical data</b>	
Contact resistance	≤ 5 mΩ
Rated current In	4 A per socket / 12 A max. at 40°C
Nominal voltage	10 - 30 V DC
Rated voltage	32 V
Insulation resistance	> 1 GΩ
<b>Approvals</b>	
Approvals	cURus
<b>Scope of delivery and accessories</b>	
Scope of delivery	ZVK: 2 dust covers for unused sockets ZBS: 10 attachable labels

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.

