




**Product information**  
**0906 UTP 301**  
**2236**

<b>Name</b>	
	0906 UTP 301
	
	T-connector with 7/8" male/female connector, 5 poles (especially suitable for DeviceNet modules with 7/8" bus connection)
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Type</b>	0906 UTP 301
<b>Order No.</b>	2236
<b>Description</b>	T-connector with 7/8" male/female connector, 5 poles (especially suitable for DeviceNet modules with 7/8" bus connection)
<b>Number of contacts</b>	5
<b>Color of housing</b>	yellow
<b>Product characteristics</b>	Vibration resistance, Oil resistance
<b>Classification</b>	
<b>Belden brand</b>	Lumberg-Automation
<b>Environmental conditions</b>	
<b>Environmental temperature</b>	-25 °C ... 90 °C
<b>Degree of protection (IP), mounted</b>	IP67
<b>Pollution degree</b>	3
<b>Materials</b>	
<b>Housing material / Molded body</b>	TPU
<b>Contact material</b>	CuZn
<b>Contact material - Surface refinement</b>	pre-nickeled and 0.8 microns gold-plated
<b>Knurled screw / nut material</b>	Al black anodized
<b>Electrical data</b>	
<b>Contact resistance</b>	≤ 5 mΩ
<b>Rated current I<sub>n</sub></b>	9 A at 40 °C
<b>Nominal voltage</b>	300 V
<b>Insulation resistance</b>	> 1 GΩ



Picture  
Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.