



**Product information**  
**0970 PSL 112**  
**27076**

<b>Name</b>	
0970 PSL 112	
	
Profibus-DP device with 8 digital outputs to connect standard actuators, combined FIXCON/M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.	
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Type</b>	0970 PSL 112
<b>Order No.</b>	27076
<b>Description</b>	Profibus-DP device with 8 digital outputs to connect standard actuators, combined FIXCON/M12 socket, rotary switches for addressing, M12 bus connection, M23 power supply.
<b>Note</b>	The application of these products in harsh environments should always be checked before use.
<b>Color of housing</b>	orange
<b>Product characteristics</b>	Oil resistance, EMV resistance, Vibration resistance
<b>Classification</b>	
<b>Belden class</b>	I/O Modules with Digital Outputs (DO)
<b>Belden brand</b>	Lumberg-Automation
<b>Mechanical data</b>	
<b>Weight</b>	535 g
<b>Dimensions (W x H x D)</b>	60 mm x 179 mm x 51.3 mm
<b>Environmental conditions</b>	
<b>Environmental temperature</b>	0 °C ... 60 °C
<b>Degree of protection (IP), mounted</b>	IP67
<b>Materials</b>	
<b>Housing material / Molded body</b>	PUR
<b>Approvals</b>	
<b>Approvals</b>	UL
<b>Bus system</b>	
<b>Fieldbus system</b>	Profibus DP
<b>Bus Connection</b>	M23
<b>Device Identification</b>	044D hex
<b>Transmission rate</b>	12 MBd
<b>Address range</b>	1 dec. ... 126 dec.
<b>Rotary address switches</b>	1 dec. ... 99 dec.
<b>Default address</b>	99 dec.
<b>System power supply</b>	
<b>System power supply</b>	U <sub>L</sub>
<b>Nominal voltage (System power supply)</b>	24 V DC
<b>Voltage range DC (System power supply)</b>	19 V ... 30 V
<b>Power consumption (System power supply)</b>	60 mA
<b>Reverse polarity protection (System power supply)</b>	Yes
<b>Operating Indication (System power supply)</b>	LED green
<b>Actuator power supply</b>	
<b>Actuator power supply</b>	U <sub>S</sub> with potential separation
<b>Nominal voltage (Actuator power supply)</b>	24 V DC
<b>Voltage range (Output power supply)</b>	19 V ... 30 V
<b>Reverse polarity protection (Output power supply)</b>	Yes


The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Indication (Output power supply)	LED green
<b>Outputs</b>	
Output wiring	Type 2 A acc. to IEC 61131-2
Signal type (Outputs)	Digital Outputs
Number of channels (Outputs)	8
Channel type (Outputs)	N.O., p-switching
Nominal output current per channel	2 A
Short-circuit proof (Outputs)	Yes
Max. output current per module (Outputs)	15 A
Overload-proof (Outputs)	Yes
Channel status indicator (Outputs)	LED yellow per channel
Diagnostic indication (outputs)	LED red per channel
<b>Scope of delivery and accessories</b>	
Scope of delivery	Dust covers M12 - 2 pieces, Attachable labels - 10 pieces

**Picture**

**Drawing**



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.