



## Product information Double female connector - ZV 2 4-3-225/2 M 43782


Name	Double female connector
	M12 Double female connector (2 port distributor), with self-locking threaded joint, 3 poles, with molded cable, 2 meter, PUR jacket, halogen free, black.
Delivery informations	
Availability	available
Product description	7/0 4 0 005/0 M
Type	ZV 2 4-3-225/2 M
Order No.	43782
Description	M12 Double female connector (2 port distributor), with self-locking threaded joint, 3 poles, with molded cable, 2 meter, PUR jacket, halogen free, black.
Number of contacts	3
Color of housing	orange
Product characteristics	Vibration resistance, Oil resistance, Drag chains suitable
Classification	
Belden brand	Lumberg-Automation
Environmental conditions	
Environmental temperature	-25 °C 80 °C
Degree of protection (IP), mounted	IP67
Pollution degree	3
Materials	
Housing material / Molded body	TPU, self-extinguishing
Contact bearer material	TPU, self-extinguishing
Contact material	CuZn
Contact material - Surface refinement	pre-nickeled and 0.8 microns gold-plated
Knurled screw / nut material	CuZn, nickel-plated
Sealing material	FKM
Electrical data	
Contact resistance	≤5 mΩ
Rated current In	2 A at 40 °C
Nominal voltage	60 V
Rated voltage	63 V
Test voltage	2.0 kV eff./60 s
Insulation resistance	>1 GΩ
Cable	
Cable length	2 m
Cable number	225
Cable description	Cable for sensors and actuators
Color of jacket	black
Without halogens as in EN 50267-2-3	<b>→</b>
Material of outer jacket	PUR
Outer diameter of the cable	4.7 mm
Nominal diameter of the cable - amount	4
Nominal diameter of the cable - diameter	0.34 mm <sup>2</sup>
Diameter of conductor - Number	43
Diameter of conductor	0.10 mm
Flame resistant according to standard	yes

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect



Picture

Drawing



The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.