



**Product information**  
**0905 356 312/0,6 M**  
**75619**

<b>Name</b>	
0905 356 312/0,6 M	
	
Power supply double, molded on both sides with 7/8" male connector and 7/8" female connector, 4 poles, 0.6 m.	
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Type</b>	0905 356 312/0,6 M
<b>Order No.</b>	75619
<b>Description</b>	Power supply double, molded on both sides with 7/8" male connector and 7/8" female connector, 4 poles, 0.6 m.
<b>Note</b>	The application of these products in harsh environments should always be checked before use.
<b>Color of housing</b>	black
<b>Product characteristics</b>	Oil resistance
<b>Classification</b>	
<b>Belden class</b>	Power Supply Cable
<b>Belden brand</b>	Lumberg-Automation
<b>Cable</b>	
<b>Cable length</b>	0.6 m
<b>Cable number</b>	356
<b>Cable description</b>	Control cable
<b>Color of jacket</b>	black
<b>Material of outer jacket</b>	PUR
<b>Without halogens as in EN 50267-2-3</b>	✓
<b>shielded</b>	✗
<b>welding spark proof</b>	✗
<b>Outer diameter of the cable</b>	7.2 mm
<b>Number of conductors</b>	4
<b>Cable design</b>	4 x 1.0 mm <sup>2</sup>
<b>Conductor design</b>	finest stranding, 56 x ø 0.15 mm
<b>Flame resistant according to standard</b>	IEC 60332-2, CSA FT-2