



Product information
OZD Genius G12
933 989-021

Name	
OZD Genius G12	
	
interface converter electrical/optical for Genius field bus networks; repeater function; for quartz glass und PCF (HCS) FO; approval for Ex-zone 2 (Class 1, Div. 2)	
Delivery informations	
Availability	available
Product description	
Description	interface converter electrical/optical for Genius field bus networks; repeater function; for quartz glass und PCF (HCS) FO; approval for Ex-zone 2 (Class 1, Div. 2)
Port type and quantity	2 x optical: 4 sockets BFOC 2.5 (STR); 1 x electrical: 4-pin connector with self-locking mechanism
Type	OZD Genius G12
Order No.	933 989-021
Electrical interface	
Signal type	Geniusbus
Bit rate	38.4; 76.8; 153.6 kbit/s
Signal delay time (optional input/output)	800 ns
Input/output signal	Geniusbus
Genius cable	length: >250 m attenuation at 1 MHz: <8 dB for 150 Ohm cable <5 dB for 100 Ohm cable
Connection capability	max. 32 terminal devices
Terminator	external
Galvanic isolation	shielding in/shielding out: yes; data lines/housing: yes
Optical interface	
Wavelength	860 nm
Cascadability	not limited
More Interfaces	
Power supply	5-pin terminal block, screw mounting
Signaling contact	5-pin terminal block, screw mounting
Network size - length of cable	
Single mode fiber (SM) 9/125 µm	-
Multimode fiber (MM) 50/125 µm	2700 m 11 dB link budget at 860 nm; A = 3 dB/km, 3 dB reserve
Multimode fiber (MM) 62.5/125 µm	2600 m 12 dB link budget at 860 nm; A = 3.5 dB/km, 3 dB reserve
Multimode fiber HCS (MM) 200/230 µm	1500 m 16 dB link budget at 860 nm; A = 8 dB/km, 3 dB reserve
Power requirements	
Operating voltage	24 VDC (19 ... 35 VDC), non-interchangeable, safety extra-low voltage
Current consumption	130 mA
Power consumption	3.1 W
Redundancy	
Redundancy functions	HIPER-Ring (ring structure), redundant 24 V infeed
Ambient conditions	
Operating temperature	0 °C to +55 °C
Storage/transport temperature	-40 °C to +80 °C
Relative humidity	<95% (non-condensing)

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.



Mechanical construction	
Dimensions (W x H x D)	40 x 111 x 73.5 mm
Mounting	DIN rail or mounting plate
Weight	500 g
Protection class	IP 40
Housing material	die-cast zinc
Approvals	
Issued or requested approvals	cUL508, cUL1604 Class1, Div. 2, Groups A,B,C and D
Scope of delivery and accessories	
Scope of delivery	device, start-up instructions
Accessories to order separately	manual, order no. 933 989-901

The information published has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price related/commercial respect.