



**Product information**  
**M4-S-24VDC 300W**  
**943 871-001**

<b>Name</b>	
M4-S-24VDC 300W	
	
Power supply for MACH 4002 chassis with two inputs for redundant power supply	
<b>Delivery informations</b>	
<b>Availability</b>	available
<b>Product description</b>	
<b>Description</b>	Power supply for MACH 4002 chassis with two inputs for redundant power supply
<b>Order No.</b>	943 871-001
<b>Type</b>	M4-S-24VDC 300W
<b>Service</b>	
<b>Diagnostics</b>	LEDs (P1 und P2) at basic device
<b>Technical data</b>	
<b>Operating voltage</b>	24 V DC (19,2 V - 32 V)
<b>Operating temperature</b>	0°C to +60°C
<b>Nominal power of voltage supply</b>	380 W
<b>Power requirements</b>	
<b>Current consumption</b>	max. 21 A (24 V DC)
<b>More Interfaces</b>	
<b>Voltage input</b>	plug-in terminal block
<b>Approvals</b>	
<b>Safety of industrial control equipment</b>	cUL 508
<b>Safety of information technology equipment</b>	cUL 60950-1
<b>Shipbuilding</b>	Germanischer Lloyd
<b>Scope of delivery and accessories</b>	
<b>Scope of delivery</b>	device, manual