

T-connectors and Adapters

2-way Distributors, M8 and M12 T-connectors

ZV 2						
	M12	A	B	Double female connector (2 port distribution box), with self-locking threaded joint, 3 poles, with molded cable	Type	Order No.
					ZV 2 4-3-225/2 M	43782
				Outer jacket material: 225 = PUR halogen-free, black	ZV 2 4-3-225/5 M	43783
					ZV 2 4-3-225/10 M	43780
ASBS 2 M8						
	M12	M8 A	M8 B	T-connector/splitter, 2-way, M8 male connector with two M8 female connectors, 3 poles, with self-locking threaded joint	Type	Order No.
					ASBS 2 M8	11124
ASBS 2 M12 ASBSA 2 M12						
	ASBSA 2 M12-3	A	B	T-connector/splitter, 2-way, M12 male connector with two M12 female connectors, 3 and 5 poles, with self-locking threaded joint	Type	Order No.
					ASBSA 2 M12-3	58911
	ASBS 2 M12-5	A	B	ASBS 2 M12-5 1-1: wired through 1 to 1 with AND circuit	ASBS 2 M12-5S	11122
					ASBS 2 M12-5	11120
	ASBS 2 M12-5S	A	B		ASBS 2 M12-5 1-1	68008
						
ASBS 2 M8-90						
	M12	M8 A	M8 B	T-connector/splitter, 2-way, M12 male connector with two M8 female connectors, 3 poles, 90°-version, with self-locking threaded joint	Type	Order No.
					ASBS 2 M8-90	11125
ASBS 2 M12...-90						
	ASBS 2 M12-4S-90	A	B	T-connector/splitter, 2-way, M12 male connector with two M12 female connectors, 4 and 5 poles, 90°-version, with self-locking threaded joint	Type	Order No.
					ASBS 2 M12-4S-90	11119
	ASBS 2 M12-5-90	A	B		ASBS 2 M12-5-90	11121
						
FASBS 2 M12						
	M12	A	B	T-connector/splitter, 2-way, M12 male connector with two M12 female connectors, 5 poles, with mounting hole	Type	Order No.
					FASBS 2 M12-5S	51645
0906 UTP 101						
	M12	A	B	T-connector/splitter, 2-way, M12 female connector with M12 male and female connector, 5 poles	Type	Order No.
					0906 UTP 101	7843
				– especially suitable for DeviceNet and CANopen® modules with M12 bus connection –		
0906 UTP 104						
	M12	A	B	T-connector/splitter, 2-way, M12 female connector with two M12 male connectors, 5 poles, with mounting hole	Type	Order No.
					0906 UTP 104	98611
				– especially suitable to connect 24 V intermediate power supply with Lion-Link-I/O modules –		

T-connectors and Adapters

7/8" and M23 T-connectors

0906 UTP 301

T-connector/splitter with one 7/8" female and two 7/8" male/female connectors, 5 poles

Type	Order No.
0906 UTP 301	2236

– especially suitable for DeviceNet modules with 7/8" bus connection –

**0906 UTP 302**

T-connector/splitter with one M12 female and two 7/8" male/female connectors, 5 poles

Type	Order No.
0906 UTP 302	16588

– especially suitable for DeviceNet and CANopen® modules with M12 bus connection –

**0906 UTP 303 | 0906 UTP 312**

T-connector/splitter with one 7/8" female and two 7/8" male/female connectors

Type	Order No.
0906 UTP 303	3047
0906 UTP 312	103783

0906 UTP 303: 3 poles, especially suitable for DeviceNet and CANopen® modules with 7/8" bus connection

0906 UTP 312: 4 poles, especially suitable for Auxiliary Power with 7/8" power connection

**0906 UTP 201**

T-connector for power supply with M23 male/female connector, 6 poles

Type	Order No.
0906 UTP 201	6906

– especially suitable for Profibus and Interbus modules –

0906 UTP 202

T-connector with M23 male/female connector, 12 poles

Type	Order No.
0906 UTP 202	2298

– especially suitable for Profibus modules with M23 bus connection for separate feeding of power supply (system/sensor system) and Profibus signals –

0906 UTP 203

T-connector for power supply with M23 male/female connector, 6 poles

Type	Order No.
0906 UTP 203	43940

0906 UTP 204

T-connector for separate feeding of the power supply at installation remote bus modules with M23 male/female connector, 9 poles

Type	Order No.
0906 UTP 204	43941

– especially suitable for Interbus installation remote bus modules –

T-connectors and Adapters

Double Solenoid Valve Adapter, Connector for Pressure Switches, Valve Adapters

VAD M12 1A-VAD 1A-1-3

Double solenoid valve adapter (valve adapter with integrated M12 male receptacle connector), according to DIN EN 175301-803, form A, with LED function indicator and varistor for voltage protection, connected protective earth

Outer jacket material:

226 = PUR halogen-free, black

241 = PUR halogen-free, welding spark proof, black

Type	Order No.
VAD M12 1A-VAD 1A-1-3-226/0.4 M	12180
VAD M12 1A-VAD 1A-1-3-241/0.4 M	12181

VAD 3C-4-1a

Connector for pressure switches according to DIN EN 175301-803, form A, with LED operation and function indicator, with M12 male receptacle connector

Type	Order No.
VAD 3C-4-1-M12-5	46568

VAD 1A...M12

Valve adapter according to DIN EN 175301-803, form A, with LED function indicator, protection circuit with varistor, connected protective earth, with M12 male receptacle connector

Type	Order No.
VAD 1A-1-3-M12-5	12141

VAD 1A...M8

Valve adapter according to DIN EN 175301-803, form A, with LED function indicator, protection circuit with varistor, connected protective earth, with M8 male receptacle connector

Type	Order No.
VAD 1A-1-3-M8-3	12142

VB 1A...M8

Valve adapter according to DIN EN 175301-803, form B, with LED function indicator, protection circuit with varistor, connected protective earth, with M8 male receptacle connector

Type	Order No.
VB 1A-1-2-M8-3	12198